

### YILDIZ GEMİ A.Ş. / PERINI NAVI SRL

- C2086 S/Y ASAHI 56m (iskele-sancak *portside-starboardside*)  
C2095 S/Y SALUTE 56m (iskele-sancak *portside-starboardside*)  
C2106 S/Y SILVANA 56m (iskele-sancak *portside-starboardside*)  
C2123 S/Y PANTHALASSA 56m (iskele-sancak *portside-starboardside*)  
C2126 S/Y MELEK 56m (iskele-sancak *portside-starboardside*)  
C2132 S/Y 56m (iskele-sancak *portside-starboardside*)



#### GENEL ÖZELLİKLER

- G 6640 mm - B 2650 Net Açıklık
- ABS / MCA onaylı
- Tık kaplamaya uygun yüzey menteşeler
- Hidrolik açma / kapama
- Hidrolik pençe kilitler
- Serpinti geçirmez tasarım
- Baskı tipi conta
- Her iki kapağı da kontrol eden ortak güç ünitesi
- Radyo kontrollü uzaktan kumanda
- 1 dakikalık açılma veya kapanma süresi

#### MALZEME BİLGİSİ

**Kapak:** Alüminyum  
**Kasa:** Paslanmaz Çelik  
**Kilit ve Menteşeler:** Paslanmaz Çelik

#### AĞIRLIK BİLGİSİ

**Kapak:** 1400 kg  
**Kasa:** 500 kg

#### SİSTEM BİLEŞENLERİ

- Yapısal Kapak
- Yapısal Kasa
- Yüzey Menteşeler
- Hidrolik Kaldırma Siliindirleri
- Pençe Kilitler
- Elektrik Kontrol Sistemi
- Pozisyon Sensörleri
- Uzaktan Kumanda

#### MAIN FEATURES

- W 6640 mm - L 2650 mm Clear Opening
  - ABS / MCA approved
- Surface hinges suitable for teak layer
  - Hydraulic opening / closing
  - Hydraulic claw locks
  - Weathertight design
  - Compression type gasket
- Common power pack serving both hatches
  - Radio remote control
  - 1-minute opening or closing time

#### MATERIAL INFORMATION

**Door:** Aluminium  
**Frame:** Stainless Steel  
**Locks and Hinges:** Stainless Steel

#### WEIGHT INFORMATION

**Door:** 1400 kg  
**Frame:** 500 kg

#### SYSTEM COMPONENTS

- Door Construction
- Frame Construction
- Surface Hinges
- Hydraulic Lifting Cylinders
- Hydraulic Claw Locks
- Electric Control System
  - Position Sensors
  - Remote Control