



### GENEL ÖZELLİKLER

- B 5000 mm x Y 2600 mm Net Açıklık
- LR / MCA onaylı
- Gizli menteşeler
- Hidrolik açma / kapama ve kilitleme
- Su geçirmez tasarım
- Baskı tipi conta
- Sabit ve radyo kontrollü uzaktan kumanda
- 8 kişilik yüke (600 kg) dayanım
- 1 dakikalık açılma veya kapanma süresi

### MALZEME BİLGİSİ

**Kapak:** Paslanmaz Çelik

**Kasa:** Paslanmaz Çelik

**Kilit ve Menteşeler:** Paslanmaz Çelik

### AĞIRLIK BİLGİSİ

**Kapak:** 4500 kg

**Kasa:** 4500 kg

### SİSTEM BİLEŞENLERİ

- Yapısal Kapak
- Yapısal Kasa
- Menteşeler
- Hidrolik Kaldırma Silindirleri
- Hidrolik Kilit Silindirleri
- Elektrik Kontrol Sistemi
- Pozisyon Sensörleri
- Uzaktan Kumanda

### MAIN FEATURES

- L 5000 mm x H 2600 mm Clear Opening
  - LR / MCA approved
  - Concealed hinges
- Hydraulic opening / closing and locking
  - Watertight design
  - Compression type gasket
  - Fixed and radio remote control
  - Durable to 8 person load (600 kg)
  - 1-minute opening or closing time

### MATERIAL INFORMATION

**Door:** Stainless Steel

**Frame:** Stainless Steel

**Locks and Hinges:** Stainless Steel

### WEIGHT INFORMATION

**Door:** 4500 kg

**Frame:** 4500 kg

### SYSTEM COMPONENTS

- Door Construction
- Frame Construction
  - Hinges
- Hydraulic Lifting Cylinders
- Hydraulic Locking Cylinders
- Electric Control System
  - Position Sensors
  - Remote Control