



#### GENEL ÖZELLİKLER

- G 2800 mm x Y 1620 mm Net Açıklık
- ABS / MCA onaylı
- Hidrolik tahrikli G menteşeler
- Hidrolik açma / kapama ve kilitleme
- Su geçirmez tasarım
- Pnömatik conta
- Radyo kontrollü uzaktan kumanda
- 1 dakikalık açılma veya kapanma süresi

#### MALZEME BİLGİSİ

**Kapak Konstrüksiyonu:**

Alüminyum

**Kasa Konstrüksiyonu:**

Çelik, Paslanmaz Çelik

**Kilit ve Menteşeler:**

Paslanmaz Çelik

#### AĞIRLIK BİLGİSİ

**Kapak:** 400 kg

#### SİSTEM BİLEŞENLERİ

- G Menteşeler
- Hidrolik Kaldırma Silindirleri
- Hidrolik Kilit Silindirleri
- Elektrik Kontrol Sistemi
- Hidrolik Valf Bloğu
- Pnömatik Valf Bloğu
- Pozisyon Sensörleri
- Uzaktan Kumanda

#### MAIN FEATURES

- W 2800 mm x Y 1620 mm Clear Opening
  - ABS / MCA approved
  - Hydraulic driven G hinge
- Hydraulic opening / closing and locking
  - Watertight design
  - Pneumatic gasket
  - Radio remote control
- 1-minute opening or closing time

#### MATERIAL INFORMATION

**Door Construction:**

Aluminium

**Frame Construction:**

Steel, Stainless Steel

**Locks and Hinges:**

Stainless Steel

#### WEIGHT INFORMATION

**Door:** 400 kg

#### SYSTEM COMPONENTS

- G Hinges
- Hydraulic Lifting Cylinders
- Hydraulic Locking Cylinders
- Electric Control System
- Hydraulic Valve Block
- Pneumatic Valve Block
- Position Sensors
- Remote Control